

I hereby certify that this correspondence is being deposited with the U.S. Postal Service with sufficient postage as First Class Mail in an envelope addressed to: Assistant Commissioner for Patents, Washington, D.C., 20231, on:

Date: October 5, 2001

By: Jennifer Mahoney

DOCKET NO.: 37128.8007.US

**IN THE UNITED STATES PATENT AND TRADEMARK OFFICE**

IN RE APPLICATION OF:

Jiang and Chang

SERIAL NO.: 09/932,439

FILED: 16 August 2001

FOR: **METHOD AND SYSTEM FOR WIRELESS  
VOICE CHANNEL/DATA CHANNEL  
INTEGRATION**

EXAMINER: Not yet Assigned

ART UNIT: Not yet Assigned

**PRELIMINARY AMENDMENT**

Assistant Commissioner for Patents  
Washington, D.C. 20231

Sir:

Prior to examination of the above-referenced application, please amend the application as follows:

**In the Drawings:**

Please add figure 9D and Figure 12D. No new matter is added. Figures 9D and 12D contain information originally submitted in Figures 9 and 12. Figures 9 and 12 required an additional sheet to comply with formatting requirements of 37 C.F.R. §1.84.

**In the Specification:**

On page 5, please add the following paragraph [0030.1] after paragraph [0030] as follows:

**Figure 9D** is a list of XML tags in one embodiment.

On page 5, please add paragraph [0038.1] after paragraph [0038] as follows:

**Figure 12D** is a list of XML tags in one embodiment.

On page 31, please replace the paragraph [00160] with the following rewritten paragraph:

Any file or text to be played to the end user is specified as a .wav file, a .txt file, or text in double quotes. **Figures 9A-9D** provide more detail regarding the incall XML tags. **Figures 10A and 10B** list example XML files that illustrate the use of the tags in the XML sent by a customer application to the incall agent.

On page 42, please replace paragraph [00206] with the following rewritten paragraph:

The customer must supply the XML file that drives outcall service. The customer may build this XML file in any way, but for the purposes of this document, we assume that the XML file is built through some sort of automated application (e.g., a customer application). This application then sends the XML file to the outcall service via an HTTP request. The tags for the XML file are detailed in **Figures 12A-12D**. **Figures 13A and 13B** list example XML files that illustrate the use of the tags in an XML file sent by a customer application to the outcall agent.

On page 45, please replace paragraph [00226] with the following rewritten paragraph:

An HTTP request with a reset tag set in an XML tag will cancel the values for that tag and any of its child tags. Only certain tags, such as service and call tags, may be specified for reset. **Figures 12A-12D** show detail for the outcall XML tags. If a service is canceled, all calls specified for that service will be canceled. Calls in progress at the time of the request will be completed. If a call is canceled, only that call will be removed from the queue. The ID for this HTTP request must match the ID for the HTTP request that contained the M-file or P-file that specified the service or call to be canceled.


**REMARKS**

The specification has been amended to reflect a change in the numbering of the drawings. Specifically, Figures 9A-9C are now numbered 9A-9D and Figures 12A-12C are now numbered 12A-12D. No new matter is added by these amendments.

No further fees are believed necessary with this communication. However, the Commissioner is hereby authorized and requested to charge any deficiency in fees herein to Deposit Account No. 50-0665.

Respectfully submitted,

Date: 10-5-01

  
Barbara B. Courtney, Registration No. 42,442

**Correspondence Address:**

Customer Number 22918


Phone: (650) 838-4300

**Version with markings to show changes made**

Any file or text to be played to the end user is specified as a .wav file, a .txt file, or text in double quotes. **Figures 9A-9[C]D** provide more detail regarding the incall XML tags. **Figures 10A and 10B** list[s] example XML files that illustrate the use of the tags in the XML sent by a customer application to the incall agent.

The customer must supply the XML file that drives outcall service. The customer may build this XML file in any way, but for the purposes of this document, we assume that the XML file is built through some sort of automated application (e.g., a customer application). This application then sends the XML file to the outcall service via an HTTP request. The tags for the XML file are detailed in **Figures 12A-12[C]D**. **Figures 13A and 13B** list[s] example XML files that illustrate the use of the tags in an XML file sent by a customer application to the outcall agent.

An HTTP request with a reset tag set in an XML tag will cancel the values for that tag and any of its child tags. Only certain tags, such as service and call tags, may be specified for reset. **Figures 12A-12[C]D** show detail for the outcall XML tags. If a service is canceled, all calls specified for that service will be canceled. Calls in progress at the time of the request will be completed. If a call is canceled, only that call will be removed from the queue. The ID for this HTTP request must match the ID for the HTTP request that contained the M-file or P-file that specified the service or call to be canceled.



16 / 52

Element:	Incall Service
Attributes:	title
Children:	Service
Description:	A container. A high level tag that marks the start and end of the XML file. Required.
Element:	Service
Attributes:	name
Parents:	Incall Service
Children:	DNIS   Service_description   Multicall   Percall   Reset
Description:	A container. The parameters in this container describe a service running on a particular phone line (DNIS). Each line running Incall Service must have a service described for that line. Required.
Element:	DNIS
Parents:	Service
Description:	The number the caller dialed to reach the application. Required.
Element:	Service_description
Parents:	Service
Description:	Audio. The description of the service. This audio is played to reassure the caller that they have dialed the right number. Fits the carrier phrase, "Hello. You have reached <System_description>." Required.
Element:	Multicall
Parents:	Service
Children:	Call_info   Authentication   Content   Choices Value_entry
Description:	A container. The parameters specified in Multicall are to be used as default values for all the calls for the service specified in Service. Any tag may be specified in Multicall. Parameters set here act as default values for all calls for that service until another Multicall file for that service is specified. Optional.
Element:	Percall
Parents:	Service
Children:	Call
Description:	A container. Contains the list of calls to be made, one call per Call tag. Required if no Multicall tag specified.
Element:	Call
Attributes:	id
Parents:	Percall
Children:	Call_info   Authentication   Content   Choices   Value_entry   Reset
Description:	A container. Contains information for a specific call. Required if there is a Percall tag.

FIG. 9A

<b>Element:</b>	<b>Reset</b>
<b>Parents:</b>	<b>Service   Call</b>
<b>Description:</b>	Resets/Cancels a particular call (if used as a child for <b>Call</b> ) or all potential call for a particular service (if used as a child for <b>Service</b> ). Optional.
<b>Element:</b>	<b>Call_info</b>
<b>Parents:</b>	<b>Multicall   Call</b>
<b>Children:</b>	<b>Phone_number   Response_url</b>
<b>Description:</b>	A container. Contains information about the call, beyond the dialog. Required in either <b>Multicall</b> or <b>Call</b> or both.
<b>Element:</b>	<b>Authentication</b>
<b>Parents:</b>	<b>Multicall   Call</b>
<b>Children:</b>	<b>Authentication_code_description   Authentication_code   Expected_caller</b>
<b>Description:</b>	A container. Contains tags that specify the information necessary for ensuring that the caller is authorized to use the service. Authentication is indicated if there is an <b>Authentication_code</b> passed in from the customer's application. If there is an <b>authentication_code</b> , there must also be a description of that code. Optional.
<b>Element:</b>	<b>Content</b>
<b>Parents:</b>	<b>Multicall   Call</b>
<b>Description:</b>	Audio. The content message to be played to the caller. The content may be an audio file (*.wav), a text file (*.txt), or raw text (enclosed in double quotes). Optional.
<b>Element:</b>	<b>Value_entry</b>
<b>Parents:</b>	<b>Multicall   Call</b>
<b>Attributes:</b>	<b>mindigits   maxdigits</b>
<b>Description:</b>	Audio. A description of the entry to be entered by the called party. Must fit carrier phrase, "Please enter..." and "You will be asked for..." Either <b>Choices</b> or <b>Value_entry</b> , but not both, may be specified. Optional.
<b>Element:</b>	<b>Choices</b>
<b>Parents:</b>	<b>Multicall   Call</b>
<b>Children:</b>	<b>Choice   Transfer</b>
<b>Description:</b>	A container. Contains information about the list of choices that will be presented to the caller during the call. Optional.
<b>Element:</b>	<b>Phone_number</b>
<b>Parents:</b>	<b>Call_info</b>
<b>Description:</b>	Phone number from which <b>Expected_caller</b> is expected to call. Required.

FIG. 9B

Element:	Expected_caller
Parents:	Authentication
Description:	Audio. The name of the person expected to be calling from a given phone number. Optional.

Element:	Response_url
Parents:	Call_info
Description:	URL that Incall Service is to use to return status information about the call to the customer application. Optional.
Element:	Authentication_code_description
Parents:	Authentication
Description:	Audio. Description of the authentication code the caller will be asked to enter. Fits the carrier phrase, "Please enter <authentication_code_description>." For example, "Please enter your account number." Required for each Authentication tag.
Element:	Authentication_code
Parents:	Authentication
Description:	The digit string value of the caller's authentication_code_description. That is, the Authentication_code is the value that the caller must enter in order to continue with the call. Required for each Authentication tag.
Element:	Choice
Parents:	Choices
Children:	Choice_description   Choice_value
Description:	A container. Describes the choices that are available to the caller. There is usually more than one Choice tag per Choices tag. Optional.
Element:	Transfer
Parents:	Choices
Children:	Transfer_description   Transfer_number
Description:	A container. Describes the transfer option available to the caller. If there is a transfer option, the value that the caller presses is "0" in order to transfer. Only one Transfer tag is allowed per Choices tag. Optional.
Element:	Choice_description
Parents:	Choice
Description:	Audio. Describes the option the caller may choose. Fits the carrier phrase, "If you would like <choice_description>, press one." Required for each Choice tag.

FIG. 9C

Element:	Choice_value
Parents:	Choice
Description:	A single digit number that indicate the touch-tone that the caller should press in order to select the associated choice. Note that if there is a Transfer tag, "0" cannot be used for a Choice_value. Required for each Choice tag.
Element:	Transfer_description
Parents:	Transfer
Description:	Audio. Describes the person or thing (e.g., IVR) the caller would be transferred to should they press zero. Required for each Transfer tag.
Element:	Transfer_number
Parents:	Transfer
Description:	The phone number to which the caller would be transferred, if they press zero. Required for each Transfer tag.

FIG. 9D



Element:	Outcall Service
Attributes:	title
Children:	Multicall   Percall
Description:	A container. A high level tag to mark the start and end of the XML file. Required.
Element:	Service
Attributes:	name
Parents:	Outcall Service
Children:	Service_description   Multicall   Percall   Reset
Description:	A container. The parameters in this container describe a service. There can be several services set up for Outcall. This tag allows the developer to group Multicall values. Required.
Element:	Multicall
Parents:	Service
Children:	Call_info   Introduction   Authentication   Content   Value_entry   Choices
Description:	A container. Indicates the parameters specified are to be used as default values for all the calls. Parameters set here act as default values for all calls until another multicall file is specified. Optional.
Element:	Percall
Parents:	Service
Children:	Call
Description:	A container. Contains the list of calls to be made, one call per Call tag. Required if no Multicall tag specified.
Element:	Reset
Parents:	Service   Call
Description:	Resets values for parent tag and all its children tags already specified. Useful for canceling queued calls before they're made. Optional.
Element:	Call
Attributes:	id
Parents:	Percall
Children:	Call_info   Introduction   Authentication   Content   Value_entry   Choices   Reset
Description:	A container. Contains information for a specific call. Required if there is a Percall tag.
Element:	Call_info
Parents:	Multicall   Call
Children:	Phone_number   Response_url   Ensure_completion
Description:	A container. Contains information about the call, beyond the dialog. Required in either Multicall or Call or both.

FIG. 12A

Element:	Introduction
Parents:	Multicall   Call
Children:	Recipient   Sender
Description:	A container. Contains the information for the introduction portion of the call, the sender and the desired recipient. Required in either Multicall or Call or both.
Element:	Authentication
Parents:	Multicall   Call
Children:	Authentication_code_description   Authentication_code
Description:	A container. Contains tags that specify the information necessary for ensuring that the called party is the intended recipient of the call. Optional. Authentication is indicated if there is an authentication_code passed in from the customer's application. If there is an authentication_code, there must also be a description of that code and a recipient.
Element:	Content
Parents:	Multicall   Call
Description:	Audio. The content message to be played to the called party. The content may be an audio file (*.wav), a text file (*.txt), or raw text (enclosed in double quotes). Optional.
Element:	Value_entry
Parents:	Multicall   Call
Attributes:	mindigits   maxdigits
Description:	Audio. A description of the entry to be entered by the called party. Must fit carrier phrase, "Please enter..." and "You will be asked for..." Either Choices or Value_entry, but not both, may be specified.
Element:	Choices
Parents:	Multicall   Call
Children:	Choice   Transfer
Description:	A container. Contains information about the list of choices that will be presented to the user during the call. Either Choices or Value_entry, but not both, may be specified. Optional.
Element:	phone_number
Parents:	Call_info
Description:	Phone number to be called. Must include every digit that is to be dialed. (e.g., 9 to get an outside line, 1 for long distance). Required.
Element:	Response_url
Parents:	Call_info
Description:	URL that Outcall service is to use to return status information about the call to the customer application. Optional.

FIG. 12B

Element:	Ensure_completion
Parents:	Call_info
Description:	The number of times that Outcall service will call a person back, if the person has authenticated. These callbacks increase the likelihood of the completion of a desired call that was dropped accidentally (for instance, by the network). Optional. Default is 0.
Element:	Recipient
Parents:	Introduction
Description:	Audio. Usually text to be converted to speech. Fits the carrier phrase, "This is an automated call for <Recipient> from <Sender>." If Recipient is omitted from the XML, no authentication is done; rather, the called party is asked to press 1 to continue. Optional.
Element:	Sender
Parents:	Introduction
Description:	Audio. Fits the carrier phrase, "This is an automated call from <Sender>." Required.
Element:	Authentication_code_description
Parents:	Authentication
Description:	Audio. Description of the authentication code the party called will be asked to enter. Fits the carrier phrase, "Please enter <authentication_code_description>." For example, "Please enter your account number." Required for each Authentication tag.
Element:	Authentication_code
Parents:	Authentication
Description:	The digit string value of the called party's authentication_code description. That is, the Authentication_code is the value that the called party must enter in order to continue with the call. Required for each Authentication tag.
Element:	Choice
Parents:	Choices
Children:	Choice_description   Choice_value
Description:	A container. Describes the choices that are available to the called party. There is usually more than one Choice tag per Choices tag. Optional.
Element:	Transfer
Parents:	Choices
Children:	Transfer_description   Transfer_number
Description:	A container. Describes the transfer option to the called party. If there is a transfer option, the value that the called party presses is "0" in order to transfer. Only one Transfer tag is allowed per Choices tag. Optional.

FIG. 12C

Element:	Choice_description
Parents:	Choice
Description:	Audio. Describes the option the called party may choose. Fits the carrier phrase, "If you would like <choice_description>, press 1." Required for each Choice tag.
Element:	Choice_value
Parents:	Choice
Description:	A single digit number that indicates the touch-tone that the called party should press in order to select the associated choice. Not that if there is a Transfer tag, "0" cannot be used for a Choice_value. Required for each Choice tag.
Element:	Transfer_description
Parents:	Transfer
Description:	Audio. Describes the person or thing the called party would be transferred to should they press zero. Required for each Transfer tag.
Element:	Transfer_number
Parents:	Transfer
Description:	The phone number to which the called party would be transferred, if they press zero. Required for each Transfer tag,

FIG. 12D